

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

Version 7.2

Revision Date 24.01.2022

Print Date 10.06.2022

GENERIC EU MSDS - NO COUNTRY SPECIFIC DATA - NO OEL DATA

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifiers**

Product name : Lithium carbonate

Product Number : 255823

Brand : SIGALD

REACH No. : 01-2119516034-53-XXXX

CAS-No. : 554-13-2

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : Laboratory chemicals, Manufacture of substances

**1.3 Details of the supplier of the safety data sheet**

Company : Sigma-Aldrich Pte Ltd  
(Co. Registration No. 199403788W)  
2 Science Park Drive  
#05-01/12 Ascent Building  
SINGAPORE 118222  
SINGAPORE

Telephone : +65 6890 6633

Fax : +65 6890 6639

E-mail address : TechnicalService@merckgroup.com

**1.4 Emergency telephone**

Emergency Phone # : 1-800-262-8200

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Acute toxicity, Oral (Category 4), H302

Eye irritation (Category 2), H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

**2.2 Label elements****Labelling according Regulation (EC) No 1272/2008**

Pictogram



Signal word

Warning

SIGALD- 255823


Page 1 of 10

The life science business of Merck operates as MilliporeSigma in the US and Canada



Hazard statement(s)	
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
Precautionary statement(s)	
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear eye protection/ face protection.
P301 + P312	IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
Supplemental Hazard Statements	none

### Reduced Labeling (<= 125 ml)

Pictogram	
Signal word	Warning
Hazard statement(s)	none
Precautionary statement(s)	none
Supplemental Hazard Statements	none

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Formula	:	CLi <sub>2</sub> O <sub>3</sub>
Molecular weight	:	73,89 g/mol
CAS-No.	:	554-13-2
EC-No.	:	209-062-5

Component	Classification	Concentration
<b>Lithium carbonate</b>		
CAS-No.	554-13-2	Acute Tox. 4; Eye Irrit. 2; H302, H319
EC-No.	209-062-5	
		<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.



---

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

#### General advice

Show this material safety data sheet to the doctor in attendance.

#### If inhaled

After inhalation: fresh air.

#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

#### In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

#### If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water Foam Carbon dioxide (CO<sub>2</sub>) Dry powder

#### Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

### 5.2 Special hazards arising from the substance or mixture

Nature of decomposition products not known.

Combustible.

Development of hazardous combustion gases or vapours possible in the event of fire.

Risk of dust explosion.

### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

### 5.4 Further information

Prevent fire extinguishing water from contaminating surface water or the ground water system.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.



For personal protection see section 8.

## 6.2 Environmental precautions

Do not let product enter drains.

## 6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

## 6.4 Reference to other sections

For disposal see section 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage conditions

Tightly closed. Dry.

#### Storage class

Storage class (TRGS 510): 11: Combustible Solids

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Ingredients with workplace control parameters

##### Derived No Effect Level (DNEL)

Application Area	Routes of exposure	Health effect	Value
Workers	Skin contact	Acute systemic effects	100mg/kg BW/d
Workers	Inhalation	Acute systemic effects	7,02 mg/m <sup>3</sup>
Workers	Skin contact	Long-term systemic effects	26,61mg/kg BW/d
Workers	Inhalation	Long-term systemic effects	2,34 mg/m <sup>3</sup>
Consumers	Skin contact	Acute systemic effects	50mg/kg BW/d
Consumers	Inhalation	Acute systemic effects	3,03 mg/m <sup>3</sup>

##### Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	0,8381 mg/l
Sea water	0,11 mg/l
Fresh water	1,05 mg/l
Sea sediment	0,41 mg/kg
Fresh water sediment	4,09 mg/kg
Sewage treatment plant	122,2 mg/l



## 8.2 Exposure controls

### Personal protective equipment

#### Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

#### Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm

Break through time: 480 min

Material tested:KCL 741 Dermatril® L

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm

Break through time: 480 min

Material tested:KCL 741 Dermatril® L

#### Body Protection

protective clothing

#### Respiratory protection

required when dusts are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: Filter type P2

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

#### Control of environmental exposure

Do not let product enter drains.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- |               |  |
|---------------|--|
| a) Appearance | Form: granular, powder<br>Color: white |
| b) Odor       | odorless                               |



c) Odor Threshold	No data available
d) pH	9,0 - 11,0 at 1 g/l
e) Melting point/freezing point	Melting point/range: 618 °C - lit.
f) Initial boiling point and boiling range	No data available
g) Flash point	No data available
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	No data available
k) Vapor pressure	No data available
l) Vapor density	No data available
m) Density	No data available
Relative density	No data available
n) Water solubility	8,4 g/l at 20 °C - OECD Test Guideline 105- soluble
o) Partition coefficient: n-octanol/water	Not applicable for inorganic substances
p) Autoignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: No data available
s) Explosive properties	No data available
t) Oxidizing properties	none
Particle Size Distribution	D10 = 8 µm D50 = 461 µm D90 = 977 µm Measurement method: ISO 13320 Measurement technique: laser diffraction D10 = 1,76 µm D50 = 5,47 µm D90 = 12,1 µm Measurement technique: laser diffraction

## 9.2 Other safety information

No data available



---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.

### 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

### 10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:

Fluorine

Alkaline earth metals

### 10.4 Conditions to avoid

no information available

### 10.5 Incompatible materials

No data available

### 10.6 Hazardous decomposition products

In the event of fire: see section 5

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - 525 mg/kg

Remarks: (ECHA)

LC50 Inhalation - Rat - male and female - 4 h - > 2 mg/l - dust/mist

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - male and female - > 3.000 mg/kg

(OECD Test Guideline 402)

#### Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h

(OECD Test Guideline 404)

#### Serious eye damage/eye irritation

Eyes - Rabbit

Result: Eye irritation

(OECD Test Guideline 405)

#### Respiratory or skin sensitization

Sensitisation test: - Guinea pig

Result: negative

(OECD Test Guideline 406)

#### Germ cell mutagenicity

Test Type: In vitro mammalian cell gene mutation test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative



The value is given in analogy to the following substances: Lithium hydroxide  
Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Human lymphocytes

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

The value is given in analogy to the following substances: Lithium hydroxide  
Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

The value is given in analogy to the following substances: Lithium hydroxide  
**Carcinogenicity**

No data available

### **Reproductive toxicity**

No data available

### **Specific target organ toxicity - single exposure**

No data available

### **Specific target organ toxicity - repeated exposure**

No data available

### **Aspiration hazard**

No data available

## **11.2 Additional Information**

RTECS: OJ5800000

Nausea, Anorexia., Large doses of lithium ion have caused dizziness and prostration, and can cause kidney damage if sodium intake is limited. Dehydration, weight loss, dermatological effects, and thyroid disturbances have been reported. Central nervous system effects that include slurred speech, blurred vision, sensory loss, ataxia, and convulsions may occur. Diarrhea, vomiting, and neuromuscular effects such as tremor, clonus, and hyperactive reflexes may occur as a result of repeated exposure to lithium ion., Vomiting, Cyanosis and t-wave inversion have occurred in the breast-fed infants of women receiving lithium carbonate therapy.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

---

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

Toxicity to fish	static test LC50 - Oncorhynchus mykiss (rainbow trout) - 30,3 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - Daphnia magna (Water flea) - 33 mg/l - 48 h (OECD Test Guideline 202)
Toxicity to algae	static test ErC50 - Desmodesmus subspicatus (green algae) - > 400 mg/l - 72 h (OECD Test Guideline 201)







---

## **SECTION 15: Regulatory information**

### **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

#### **Other regulations**

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable.

Take note of Dir 94/33/EC on the protection of young people at work.

### **15.2 Chemical Safety Assessment**

A Chemical Safety Assessment has been carried out for this substance.

---

## **SECTION 16: Other information**

### **Full text of H-Statements referred to under sections 2 and 3.**

H302	Harmful if swallowed.
H319	Causes serious eye irritation.

### **Further information**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See [www.sigma-aldrich.com](http://www.sigma-aldrich.com) and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact [mlsbranding@sial.com](mailto:mlsbranding@sial.com).

